



Product Description

RetroGuard™ provides ultimate stain and etch protection with a high gloss finish. This topical coating is ideal for protecting concrete and terrazzo against staining. When a spill occurs, RetroGuard's layer of protective properties prevent the floor from immediate damage and increases the window of opportunity for clean-up.

BENEFITS

- Ultimate stain and etch protection
- Topical sealer
- Strong floor adhesion; does not peel or flake
- Creates high gloss and shine when burnished; cures without burnishing
- Enhances floor color including dyes and aggregate
- UV stable; may be used outdoors
- Can be re-applied anytime; does not require stripping
- Creates sacrificial layer between spill and floor
- Reduces expensive and time consuming stain repair
- Ideal for all Ashford Formula™ and RetroPlate® treated floors—new or old, standard or colored - and all concrete and terrazzo floors



Product Selection Guide

	Retro Guard	Retro Pel	Retro Shield
Acid Protection	High	None	Medium
Oil & Water Repellency	Low	High	Medium
Dye Enhancement	High	None	High
Sheen Enhancement	High	Low	Medium
Penetrating Sealer	No	Yes	Yes
Topical Sealer	Yes	No	Yes
Ease of Installation	Medium	Easy	Easy
Ease of Repair	Medium	Medium	Easy

Technical Info

Form:	Milky white
Coverage:	1,500-2,000 ft ² /gal (37-50 m ² /L)
Packaging:	1 gal (3.79 L) Jug 5 gal (19 L) Pail 55 gal (208 L) Drum (by request)
Storage Life:	One year in factory sealed container
Freezing:	Protect from freezing
Odor:	Low odor
VOC:	VOC content 0 g/L. Complies with all known national, state and district AIM VOC regulations. Maximum VOC content 100 g/L.



Application

Read all instructions and SDS information before use. Use appropriate safety equipment. Always test floor surface for suitability and desired results before overall application. Evaluate vapor transmission, or other potential concerns. Let surface dry thoroughly before inspection and approval.

PREPARATION

Protect people, vehicles, property, plants and all surfaces not meant for treatment from product, residue, splash, fumes and wind drift. Use polyethylene or other proven protective materials. Ensure fresh air entry and cross ventilation during application and drying. Remove any dirt, oil, grease, paint, waxes, efflorescence and surface sealers before application. For best results, clean the floor with CreteClean Plus with Scar Guard™ using an auto scrubber with blue or black pads, or a mop and bucket. RetroGuard can be applied 28 days after placement of the concrete.

Surface & Air Temperature: Temperature should be between 40-80°F (4-26°C). RetroGuard applies, dries and cures more evenly on a cool floor. Avoid applying in direct sunlight. Use only in well ventilated areas.